



ATM

SERIES

THE BENCH & FLOOR SCALE





ATM

COMMON FEATURES

- OIML-R76 and EC Class III Type Approved
- Flexible Platform Collocation
- Mold Injected Aluminum Alloy Platform
- Stainless Steel Platform Cover
- Overload Protection Devices Against Excessive Load or Shock Applied
- Designed to Meet Industrial Application Requirements
- User Programmable Capacity and Division
- Equipped with Power On Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection**
- Dual Power Source: By Built-in Rechargeable Battery or Power A adaptor
- Complete with Low Battery and Charging Status Indicator
- 5 1/2 x 51mm Oversize Wide Angle LCD Digits
- Adjustable Feet, Rechargeable Battery, Bubble Level and Power Adaptor Included

**Depends on R60 approval grade of the load cell used

DISPLAY RESOLUTION: - OIML APPLICATIONS

- Standard = 3000
- Maximum = 30000 Under Extended Display Mode

DISPLAY RESOLUTION: - NON-OIML APPLICATIONS

- User Programmable
- Recommended = 6000 to 7500
- Maximum = 30000

OPTION AVAILABLE

- EL Backlight
- Printer Interface
- RS232C Interface

SPECIFICATIONS



Model No.	Capacity	Recommended Display Resolution		Platform
		OIML Application	Non-OIML Application	
ATM-B30	30kg	0.01kg	0.005kg	330 x 450mm with Stainless Steel Cover
ATM-B60	60kg	0.02kg	0.01kg	
ATM-B150	150kg	0.05kg	0.02kg	
ATM-F60	60kg	0.02kg	0.01kg	420 x 520mm with Stainless Steel Cover
ATM-F150	150kg	0.05kg	0.02kg	
ATM-F300	300kg	0.1kg	0.05kg	
ATM-L150	150kg	0.05kg	0.02kg	500 x 600mm with Stainless Steel Cover
ATM-L300	300kg	0.1kg	0.05kg	
ATM-L550	550kg	0.2kg	0.1kg	
Tare Range	OIML = 1/3 Max - e Non-OIML = Full Range			
Power Source	By Built-in Rechargeable Battery or AC/DC Power Adaptor			
Operating Environment	0° - 40°C (32° - 104° F), Non-condensed R.H. ≤ 85%			

Specifications subject to change without notice



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.
 Tel : +886-2-29189121 (12 Lines) Fax : +886-2-29181508 - 29183652 - 29112176-7
 http://www.uwe-scale.com.tw e-mail:uwe@ms8.hinet.net

Oct '2002 Designed by DARY
 Printed in Taiwan